



PC

ATX

TFX

MICRO ATX

FLEX ATX

POWER
NEVER ENDS

About FSP Group

FSP Group is the leading power supply manufacturer in the world.

Since established in 1993, the company has been committed to its R&D capability, production capacity and product quality to stand out from the competitive market.

FSP Group provides a wide variety of products related to power and electronics technology, such as adapter, open frame, SSL LED Driver, Medical, LCD TV, Industrial / Desktop computers and Servers to fit our OEM / ODM customers' needs. FSP Group is aiming to develop more and better environment friendly products continuously, including PV Inverter, UPS, ESS and battery charger products.

FSP Group's global presence in Taiwan, China, Germany, Sweden, France, India, Japan, Korea, Turkey, UK, and USA has made it easier to provide immediate support. As FSP Group is aiming to create a win-win situation, we treat our customers as friends by providing customized products and excellent service.

For FSP Group, making **Power never ends** will be our sustainable goal.

Our vision:

To be the global leading provider of green energy solutions, touch people's life, contribute to the better environment.

Our mission:

Providing the best value to customers, employees and shareholders by our innovative service and high quality products.

Energetic | **Friendly** | **Simple** | **Reliable**

POWER
NEVER ENDS



Power Your Digital Life

62368

- 01 ATX
- 06 SFX
- 07 TFX
- 08 12VO ATX
- 09 12VO SFX
- 10 12VO TFX

FORM FACTOR

ATX | AAA / ABA / ACA Series



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety	
			+3.3V	+5V	+12V	-12V	+5Vsb					
FSP550-50AAA	Intel PSDG V1.42	82% 85% 82%	Max.	20A	20A	45.83A	0.3A	2.5A	550W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0A	0A	0.1A	0A	0A				
FSP650-50AAA	Intel PSDG V1.42	82% 85% 82%	Max.	20A	20A	54A	0.3A	2.5A	650W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0A	0A	0.1A	0A	0A				
FSP750-50AAA	Intel PSDG V1.42	82% 85% 82%	Max.	20A	20A	62A	0.3A	2.5A	750W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC
			Min.	0A	0A	0.1A	0A	0A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety	
			+3.3V	+5V	+12V	-12V	+5Vsb					
FSP550-50ABA	Intel PSDG V1.42	87% 90% 87%	Max.	20A	20A	45.83A	0.3A	3A	550W		100~240 Vac	CB, CE, TUV, cUL, FCC BSMI, CCC, KC, UKCA
			Min.	0A	0A	0A	0A	0A				
FSP650-50ABA	Intel PSDG V1.42	87% 90% 87%	Max.	20A	20A	54.17A	0.3A	3A	650W		100~240 Vac	CB, CE, TUV, cUL, FCC BSMI, CCC, KC, UKCA
			Min.	0A	0A	0A	0A	0A				
FSP750-50ABA	Intel PSDG V1.42	87% 90% 87%	Max.	20A	20A	62.5A	0.3A	3A	750W		100~240 Vac	CB, CE, TUV, cUL, FCC BSMI, CCC, KC, UKCA
			Min.	0A	0A	0A	0A	0A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 150.0(L) x 150.0(W) x 86.0(H)

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety	
			+3.3V	+5V	+12V	-12V	+5Vsb					
FSP850-57ACA	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max.	20A	20A	70.83A	0.3A	3A	850W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0A	0A	0A	0A	0A				
FSP1000-57ACA	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max.	20A	20A	83.33A	0.3A	3A	1000W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0A	0A	0A	0A	0A				
FSP1200-57ACA	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max.	20A	20A	100A	0.3A	3A	1200W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0A	0A	0A	0A	0A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

ATX | ABB / ASB Series



Fan 12cm / Dimension: 150.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP650-50ABB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	54.17A 0A	0.3A 0A	2.5A 0A	650W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP750-50ABB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	62.5A 0A	0.3A 0A	2.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP850-50ABB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	2.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC, BSMI, UKCA
FSP1000-50ABB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	2.5A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, BIS, UKCA
FSP850-50ABB,GEN5	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	2.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC, BSMI, UKCA
FSP1000-50ABB,GEN5	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	2.5A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, BIS, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 130.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP850-57ASB	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	3A 0A	850W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC, BSMI
FSP1000-57ASB	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	3A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC, BSMI
FSP1200-57ASB	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	100A 0A	0.3A 0A	3A 0A	1200W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC CCC, KC, BSMI

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

ATX | AJB / AUB Series



Fan 13.5cm / Dimension: 190.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP850-50AJB	Intel PSDG V1.43	90% 92% 89%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	3A 0A	850W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP1000-50AJB	Intel PSDG V1.43	90% 92% 89%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	3A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP1200-50AJB	Intel PSDG V1.43	90% 92% 89%	Max. 20A Min. 0A	20A 0A	100A 0A	0.3A 0A	3A 0A	1200W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP850-50AJB,GEN5	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	3A 0A	850W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP1000-50AJB,GEN5	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	3A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP1200-50AJB,GEN5	Intel PSDG V2.0 ATX V3.0	90% 92% 89%	Max. 20A Min. 0A	20A 0A	100A 0A	0.3A 0A	3A 0A	1200W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 13.5cm / Dimension: 150.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP850-57AUB	Intel PSDG V2.0 ATX V3.0	92% 94% 90%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	3A 0A	850W	N/A	100~240 Vac	CB, CE, FCC, TUV cUL, BSMI, CCC, KC
FSP1000-57AUB	Intel PSDG V2.0 ATX V3.0	92% 94% 90%	Max. 20A Min. 0A	20A 0A	83.33A 0A	0.3A 0A	3A 0A	1000W	N/A	100~240 Vac	CB, CE, FCC, TUV cUL, BSMI, CCC, KC

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

ATX | AAC Series



300W-600W



750W-850W

Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP300-50AAC	Intel PSDG V1.42	82% 85% 82%	Max. 16A Min. 0A	16A 0A	25A 0A	0.3A 0A	2.5A 0A	300W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP400-50AAC	Intel PSDG V1.42	82% 85% 82%	Max. 16A Min. 0A	16A 0A	33.33A 0A	0.3A 0A	2.5A 0A	400W	80 PLUS BRONZE	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP500-50AAC	Intel PSDG V1.42	82% 85% 82%	Max. 20A Min. 0A	20A 0A	41.66A 0A	0.3A 0A	2.5A 0A	500W	80 PLUS BRONZE	100~240 Vac	CB, CE, TUV, cUL FCC, CCC, BSMI, KC, UKCA
FSP600-50AAC	Intel PSDG V1.42	82% 85% 82%	Max. 20A Min. 0A	20A 0A	50A 0A	0.3A 0A	2.5A 0A	600W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, CCC, UKCA
FSP750-50AAC	Intel PSDG V1.43	82% 85% 82%	Max. 20A Min. 0A	20A 0A	62.5A 0A	0.3A 0A	2.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, KC, BSMI
FSP850-50AAC	Intel PSDG V1.43	82% 85% 82%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	2.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, KC, BSMI

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



350W-650W



750W-850W

Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP350-51AAC	Intel PSDG V1.42	85% 88% 85%	Max. 16A Min. 0A	16A 0A	29A 0A	0.3A 0A	2.5A 0A	350W	80 PLUS BRONZE	200~240 Vac	CB, CE, TUV, UKCA
FSP450-51AAC	Intel PSDG V1.42	85% 88% 85%	Max. 16A Min. 0A	16A 0A	37.5A 0A	0.3A 0A	2.5A 0A	450W	N/A	200~240 Vac	CB, CE, TUV, UKCA
FSP550-51AAC	Intel PSDG V1.42	85% 88% 85%	Max. 20A Min. 0A	20A 0A	45.83A 0A	0.3A 0A	2.5A 0A	550W	80 PLUS BRONZE	200~240 Vac	CB, CE, TUV, CCC, UKCA
FSP650-51AAC	Intel PSDG V1.42	85% 88% 85%	Max. 20A Min. 0A	20A 0A	54.16A 0A	0.3A 0A	2.5A 0A	650W	80 PLUS BRONZE	200~240 Vac	CB, CE, TUV, CCC, UKCA, KC
FSP750-51AAC	Intel PSDG V1.43	85% 88% 85%	Max. 20A Min. 0A	20A 0A	62.5A 0A	0.3A 0A	2.5A 0A	750W	N/A	200~240 Vac	CB, CE, TUV, CCC, UKCA, KC
FSP850-51AAC	Intel PSDG V1.43	85% 88% 85%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	2.5A 0A	850W	N/A	200~240 Vac	CB, CE, TUV, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

ATX | EGN / EGA / AEC Series



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP350-50EGN	Intel PSDG V1.42	87% 90% 87%	Max. 21A Min. 0.1A	15A 0.2A	28A 0.1A	0.3A 0A	3A 0A	350W		100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP400-50EGN	Intel PSDG V1.42	87% 90% 87%	Max. 24A Min. 0.2A	15A 1A	32A 1A	0.3A 0A	3A 0A	400W		100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
FSP450-50EGN	Intel PSDG V1.42	87% 90% 87%	Max. 24A Min. 0.2A	15A 1A	36A 1A	0.3A 0A	3A 0A	450W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage						Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb				
FSP250-60EGA	Intel PSDG V1.42	87% 90% 87%	Max. 14A Min. 0.1A	15A 0.2A	17A 0.3A	17A 0.3A	0.3A 0A	3A 0A	250W		100~240 Vac	CB, CE, TUV, cUL, FCC
FSP300-60EGA	Intel PSDG V1.42	87% 90% 87%	Max. 16A Min. 0.1A	15A 0.2A	18A 0.1A	18A 0A	0.3A 0A	3A 0A	300W		100~240 Vac	CB, CE, TUV cUL, FCC, BIS

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP750-50AEC	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max. 20A Min. 0A	20A 0A	62.5A 0A	0.3A 0A	2.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV, FCC, cUL
FSP850-50AEC	Intel PSDG V2.0 ATX V3.0	87% 90% 87%	Max. 20A Min. 0A	20A 0A	70.83A 0A	0.3A 0A	2.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV, FCC, cUL

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

SFX | SAB / SBB / SAC Series



Fan 9.2m / Dimension: 100.0(L) x 125.0(W) x 63.5(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP550-57SAB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0.1A	20A 0.2A	45A 0.1A	0.3A 0A	2.5A 0A	550W	N/A	100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, KC, UKCA
FSP650-57SAB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0.1A	20A 0.2A	54A 0.1A	0.3A 0A	2.5A 0A	650W	N/A	100~240 Vac	CB, CE, TUV, cUL, FCC BSMI, CCC, KC, UKCA, EAC

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)





Fan 9.2m / Dimension: 100.0(L) x 125.0(W) x 63.5(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP750-57SBB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	62.5A 0A	0.3A 0A	2.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, KC, UKCA
FSP850-57SBB	Intel PSDG V1.42	87% 90% 87%	Max. 20A Min. 0A	20A 0A	70.83A 0.1A	0.3A 0A	2.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, KC, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 8cm / Dimension: 100.0(L) x 125.0(W) x 63.5(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety
			+3.3V	+5V	+12V	-12V	+5Vsb				
FSP250-50SAC	Intel PSDG V1.42	82% 85% 82%	Max. 12A Min. 0A	12A 0A	20.83A 0.1A	0.3A 0A	2.5A 0A	250W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, BIS, UKCA
FSP350-50SAC	Intel PSDG V1.42	82% 85% 82%	Max. 16A Min. 0A	16A 0A	29.17A 0.1A	0.3A 0A	2.5A 0A	350W		100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, UKCA
FSP450-50SAC	Intel PSDG V1.42	82% 85% 82%	Max. 16A Min. 0A	16A 0A	37.5A 0.1A	0.3A 0A	2.5A 0A	450W		100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

TFX | SGV / TAC Series



Fan 8cm / Dimension: 175.0(L) x 85.0(W) x 65.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety		
			+3.3V	+5V	+12V1	+12V2	-12V					+5Vsb	
FSP250-60SGV	Intel PSDG V1.42	87% 90% 87%	Max.	14A	15A	13A	13A	0.3A	3.0A	250W		100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0.3A	0.2A	0.1A	0.05A	0A	0A				
FSP300-60SGV	Intel PSDG V1.42	87% 90% 87%	Max.	18A	18A	13A	13A	0.3A	3.0A	300W		100~240 Vac	CB, CE, TUV, cUL, FCC
			Min.	0.3A	0.2A	0.1A	0.05A	0A	0A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 8cm / Dimension: 175.0(L) x 85.0(W) x 65.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety	
			+3.3V	+5V	+12V	-12V	+5Vsb					
FSP200-50TAC	Intel PSDG V1.42	82% 85% 82%	Max.	12A	12A	16.66A	0.3A	2.5A	200W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
			Min.	0A	0A	0.1A	0A	0A				
FSP250-50TAC	Intel PSDG V1.42	82% 85% 82%	Max.	12A	12A	20.83A	0.3A	2.5A	250W	N/A	100~240 Vac	CB, CE, TUV cUL, FCC, UKCA
			Min.	0A	0A	0.1A	0A	0.1A				
FSP300-50TAC	Intel PSDG V1.42	82% 85% 82%	Max.	16A	16A	25A	0.3A	2.5A	300W		100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, UKCA
			Min.	0A	0A	0.1A	0A	0A				
FSP350-50TAC	Intel PSDG V1.42	82% 85% 82%	Max.	16A	16A	29.18A	0.3A	2.5A	350W		100~240 Vac	CB, CE, TUV, cUL FCC, BSMI, CCC, KC, UKCA
			Min.	0A	0A	0.1A	0A	0.1A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 8cm / Dimension: 175.0(L) x 85.0(W) x 65.0(H) mm

Model No.	Ver.	Eff.	Output Voltage					Wattage	80 Plus	Input Voltage	Safety	
			+3.3V	+5V	+12V	-12V	+5Vsb					
FSP350-51TAC	Intel PSDG V1.42	82% 85% 82%	Max.	16A	16A	29.18A	0.3A	2.5A	350W		200~240 Vac	CB, CE, TUV, KC, UKCA
			Min.	0A	0A	0A	0A	0.1A				
FSP450-51TAC	Intel PSDG V1.42	82% 85% 82%	Max.	16A	16A	37A	0.3A	2.5A	450W		200~240 Vac	CB, CE, TUV, KC, UKCA
			Min.	0A	0A	0.1A	0A	0.1A				

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

12VO ATX | ARA / ARB / ARC Series



Fan 12m / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP750-27ARA	Intel PSDG 12VO V2.0	90% 92% 89%	Max. 62.5A Min. 0A	1.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV
FSP850-27ARA	Intel PSDG 12VO V2.0	90% 92% 89%	Max. 70.83A Min. 0A	1.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV
FSP1000-27ARA	Intel PSDG 12VO V2.0	90% 92% 89%	Max. 83.33A Min. 0A	1.5A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP750-27ARB	Intel PSDG 12VO V2.0	87% 90% 87%	Max. 62.5A Min. 0A	1.5A 0A	750W	N/A	100~240 Vac	CB, CE, TUV
FSP850-27ARB	Intel PSDG 12VO V2.0	87% 90% 87%	Max. 70.83A Min. 0A	1.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV
FSP1000-27ARB	Intel PSDG 12VO V2.0	87% 90% 87%	Max. 83.33A Min. 0A	1.5A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 12cm / Dimension: 140.0(L) x 150.0(W) x 86.0(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP300-20ARC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 25A Min. 0A	1.5A 0A	300W	N/A	100~240 Vac	CB, CE, TUV
FSP400-20ARC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 33.33A Min. 0A	1.5A 0A	400W	N/A	100~240 Vac	CB, CE, TUV
FSP500-20ARC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 41.66A Min. 0A	1.5A 0A	500W	N/A	100~240 Vac	CB, CE, TUV


The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

12VO SFX | SCB / SGB Series



Fan 9.2m / Dimension: 100.0(L) x 125.0(W) x 63.5(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP650-27SCB	Intel PSDG 12VO V1.1	87% 90% 87%	Max. 54A Min. 0A	1.5A 0A	650W	N/A	100~240 Vac	CB, CE, TUV, cUL FCC, CCC, KC, BSMI, UKCA
FSP750-27SCB	Intel PSDG 12VO V1.1	87% 90% 87%	Max. 62.5A Min. 0A	1.5A 0A	750W		100~240 Vac	CB, CE, TUV, cUL FCC, CCC, KC, BSMI, UKCA

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



Fan 9.2m / Dimension: 100.0(L) x 125.0(W) x 63.5(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP850-27SGB	Intel PSDG 12VO V2.0	87% 90% 87%	Max. 70.83A Min. 0A	1.5A 0A	850W	N/A	100~240 Vac	CB, CE, TUV
FSP1000-27SGB	Intel PSDG 12VO V2.0	87% 90% 87%	Max. 83.33A Min. 0A	1.5A 0A	1000W	N/A	100~240 Vac	CB, CE, TUV

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)

FORM FACTOR

12VO TFX | TRC Series



Fan 8cm / Dimension: 175.0(L) x 85.0(W) x 65.0(H) mm

Model No.	Ver.	Eff.	Output Voltage		Wattage	80 Plus	Input Voltage	Safety
			+12V	+12Vsb				
FSP300-20TRC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 25A Min. 0A	1.5A 0A	300W	N/A	100~240 Vac	CB, CE, TUV
FSP400-20TRC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 33.33A Min. 0A	1.5A 0A	400W	N/A	100~240 Vac	CB, CE, TUV
FSP500-20TRC	Intel PSDG 12VO V2.0	85% 88% 85%	Max. 41.66A Min. 0A	1.5A 0A	500W	N/A	100~240 Vac	CB, CE, TUV

The maximum power consumption in standby mode should not exceed 0.5W. (ErP* Lot 6 2013 Required)



GLOBAL OFFICE INFORMATION

FSP TECHNOLOGY INC. (Headquarters)

NO.22, Jianguo E. Rd., Taoyuan Dist., Taoyuan City 330, Taiwan

TEL : +886-3-375-9888 / FAX : +886-3-375-6966 sales@fsp-group.com.tw / www.fsp-group.com



FSP Group