

DESCRIPTION

FSP250-701US is an industrial level of switching power supply. The power supply comes to offer the total power capacity up to 250 Watts, and uses unique active PFC (Power Factor Correction) circuit design with its high-load electrical components, makes it to be perfectly used in an industrial environment. In addition, with its full range of input and output electrical features, the power supply is ideally the best choice for server, workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.



APPLICATION

For standard, advanced server, NAS and industrial power system.

FEATURES

- 80 Plus Gold
- Low Ripple & Noise
- Output over voltage protection
- Short circuit protection on all outputs
- Resettable power shut down
- INTERNAL 4 cm fan
- Dual +12V output (+12V/1, +12V/2)
- -5V is included
- 100% burn-in under high ambient temperature(50°C)
- Vacuum-impregnated transformer
- MTBF:100K hours at 25°C
- 100% Hi-pot tested
- Line input fuse protection

WATTAGE

Wattage: 250W

DIMENSION

Dimension: 190mm(L) x 100mm(W) x 40.5mm(H)

PRODUCT HIGHLIGHT

Efficiency Level: 80 Plus Gold
Altitude: 5000M

INPUT SPECIFICATION

Input Range: 90-264 Vac
Input Frequency: 47-63 Hz
Input Current: 115V@ 4.0 Amps-rms maximum,
230V@ 2.0Amps-rms maximum

GENERAL SPECIFICATION

Efficiency: 92% 230VAC
Voltage: +3.3V, +12V, +5V, +5SB: ±5%
Regulation: -12V, -5V: ±10%
Inrush Current: 50A @ 115V, or 100A @ 230V
PWOK Delay Time: 500ms > PWOK > 100ms
EMC Performance: EN61000-3-2


*Output Voltage and Current Rating

	+3.3V	+5V	+12V1	+12V2	-12V	-5V	+5Vsb
Ripple-Noise(R-P) mV	50mV	50mV	120mV	120mV	120mV	100mV	50mV
Regulation Load %	±5%	±5%	±5%	±5%	±10%	±10%	±5%
Output Max.(A)	14A	16A	16A	16A	0.5A	0.2A	3A
Output Min.(A)	0.3A	0.3A	0.5A	0.5A	0A	0A	0A

NOTES

- 5V, 3.3V, 12V, -12V Will have the regulation to 10% when all load take off.
- The +3.3V and +5V total output shall not exceed 100 watts.
- The total output shall not exceed 250 watts.
- -5V is optional.

MECHANICAL SPECIFICATION



SAFETY STANDARD APPROVAL



OUTPUT SPECIFICATION

Hold up Time: 115V/60Hz 16mSec.
Minimum@100% Load,
230V/50Hz 16mSec.
Minimum,@100% Load
+3.3Vdc output : +3.7 Vdc
minimum, + 4.8Vdc
maximum
+5Vdc output : +5.7 Vdc
minimum, + 7Vdc maximum
+12Vdc output : +13.3 Vdc
minimum, + 16Vdc
maximum

Output Rise Time: 115V-rms/230V-rms 5V
20ms Maximum
115V-rms/230V-rms 12V
20ms Maximum

Ripple & Noise: 3.3V:50mV p-p
5V:50mV p-p
12V1:120mV p-p
12V2:120mV p-p
-12V:120mV p-p
5Vsb:50mV p-p
-5V:100mV p-p

Short Circuit Protection: load < 0.1 Ohm

ENVIRONMENTAL SPECIFICATION

TEMP.Range: Storage Temperature: -20°C to + 80°C
MTBF: The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, maximum-output load, and nominal AC inout voltage