



中国国家强制性产品认证证书

证书编号：2024010907602678

认证委托人名称及地址
全汉企业股份有限公司
台湾桃园市桃园区建国东路 22 号

生产者名称及地址
全汉企业股份有限公司
台湾桃园市桃园区建国东路 22 号

生产企业名称及地址
深圳辉力电子有限公司
深圳市宝安区新安街道布心社区 73 区流塘路 352 号辉力厂 C4 栋 101 至 301、C5-C11 栋

产品名称和系列、型号、规格
开关电源供应器
见附页（仅适用于海拔 5000 米及以下；电线组件为可选）

产品标准和技术要求
GB 17625.1-2022; GB 4943.1-2022; GB/T 9254.1-2021
上述产品符合《强制性产品认证实施规则 电子产品及安全附件》
(CNCA-C09-01:2023) 的要求，特发此证。

发证日期：2025 年 08 月 11 日 有效期至：2029 年 01 月 14 日

本证书为变更证书，证书首次颁发日期：2024 年 01 月 15 日
证书信息和有效性可扫描下方二维码或登录发证机构网站查验，
也可在认监委网站（www.cnca.gov.cn）查询。

经中国合格评定国家认可委员会认可 CNAS C001-P



签发：

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





中国国家强制性产品认证证书

证书编号：2024010907602678

证书附页：第 1 页 共 1 页

(1) VITA-650GM、 VITA-650PM

交流输入：100-240V~， 8-4A， 50-60Hz

直流输出：+3.3V/20A， +5V/20A， +12V/54.17A， -12V/0.3A， +5Vsb/3.0A，
(+3.3V&+5V=100W Max) (+12V=650W Max)， (-12V=3.6W Max)， (+5Vsb=15W Max) 额定功率 650W；

(2) FSP650-57AGC 、 FSP650-57ALC

交流输入：100-240V~， 8-4A， 50-60Hz

直流输出：+3.3V/20A， +5V/20A， +12V/54.17A， -12V/0.3A， +5Vsb/3.0A，
(+3.3V&+5V=100W Max) (+12V=650W Max)， (-12V=3.6W Max)， (+5Vsb=15W Max) 总输出不可持续超过 650W；

(3) VITA-750GM 、 VITA-750PM

交流输入：100-240V~， 10-5A， 50-60Hz

直流输出：+3.3V/20A， +5V/20A， +12V/62.5A， -12V/0.3A， +5Vsb/3.0A，
(+3.3V&+5V=100W Max) (+12V=750W Max)， (-12V=3.6W Max)， (+5Vsb=15W Max) 额定功率 750W；

(4) FSP750-57AGC 、 FSP750-57ALC

交流输入：100-240V~， 10-5A， 50-60Hz

直流输出：+3.3V/20A， +5V/20A， +12V/62.5A， -12V/0.3A， +5Vsb/3.0A，
(+3.3V&+5V=100W Max) (+12V=750W Max)， (-12V=3.6W Max)， (+5Vsb=15W Max) 总输出不可持续超过 750W

本页为证书附页，应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024010907602678

NAME AND ADDRESS OF THE APPLICANT

FSP Group Inc.
No.22,JianGuo E.Rd.,TaoYuan City,TaiWan,China

NAME AND ADDRESS OF THE MANUFACTURER

FSP Group Inc.
No.22,JianGuo E.Rd.,TaoYuan City,TaiWan,China

NAME AND LOCATION OF THE FACTORY

ShenZhen HuiLi Electronics CO.,LTD
Building C4 (101~301) -C11, No. 352, LiuTang Rd., County 73, Bu'Xin Village, Xin'an, Bao'an,
Shenzhen, Guangdong, China

PRODUCT NAME,MODEL AND SPECIFICATION

Switching Power Supply
See Appendix (Altitude up to 5000m ; Cord set is optional)

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023).

Valid from: Aug.11,2025

Valid until: Jan.14,2029

Date of original issued: Jan.15,2024

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2024010907602678

Appendix: Page 1 of 1

(1) VITA-650GM、 VITA-650PM

AC Input: 100-240V~, 8-4A, 50-60Hz

DC Output: +3.3V/20A, +5V/20A, +12V/54.17A, -12V/0.3A, +5Vsb/3.0A,
(+3.3V&+5V=100W Max) (+12V=650W Max), (-12V=3.6W Max), (+5Vsb=15W Max)

Rated power 650W;

(2) FSP650-57AGC 、 FSP650-57ALC

AC Input: 100-240V~, 8-4A, 50-60Hz

DC Output: +3.3V/20A, +5V/20A, +12V/54.17A, -12V/0.3A,
+5Vsb/3.0A, (+3.3V&+5V=100W Max) (+12V=650W Max), (-12V=3.6W
Max), (+5Vsb=15W Max) The total output is unsustainable 650W;

(3) VITA-750GM 、 VITA-750PM

AC Input: 100-240V~, 10-5A, 50-60Hz

DC Output: +3.3V/20A, +5V/20A, +12V/62.5A, -12V/0.3A, +5Vsb/3.0A,
(+3.3V&+5V=100W Max) (+12V=750W Max), (-12V=3.6W Max), (+5Vsb=15W Max)

Rated power 750W;

(4) FSP750-57AGC 、 FSP750-57ALC

AC Input: 100-240V~, 10-5A, 50-60Hz

DC Output: +3.3V/20A, +5V/20A, +12V/62.5A, -12V/0.3A, +5Vsb/3.0A,
(+3.3V&+5V=100W Max) (+12V=750W Max), (-12V=3.6W Max), (+5Vsb=15W Max) The
total output is unsustainable 750W

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.