

FSP750-51AAC, GEN5

Features

- Certified CB 62368
- 80 Plus Bronze Efficiency
- Intel Design ATX 12V V3.0
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection



SAFETY STANDARD APPROVAL



DESCRIPTION

FSP 51AAC Series features with eco-friendly design, which allows 51AAC series to reach up to 88% efficiency. 51AAC series also equipped with complete protection to prevent your system from damage. 51AAC series does the job efficiently and reliably, making it a stable power supply unit built to satisfy the demands of all kind of system build.

GENERAL SPECIFICATIONS

Dimension:	140 x 150 x 86 (mm)	Environment	
(L x W x H)	5.51 x 5.91 x 3.39 (inch)		
Efficiency:	80 Plus Bronze Efficiency		
Hold-up time:	230V / 50Hz: ≥ 16ms	Working temperature:	0°C to 40°C
Operating altitude	2,000 meters above sea level	Storage temperature:	-20°C to + 70°C
MTBF:	100,000 hours of continuous operation at 25°C, Max. output load	Working humidity:	~95% RH non-condensing
		Storage humidity:	~95% RH non-condensing

INPUT SPECIFICATIONS

Input voltage:	200-240Vac
Input frequency:	50-60Hz
Input current:	200-240 Vac @ 5.5A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb
Max	20A	20A	62.5A	0.3A	2.5A
Min.	0A	0A	0A	0A	0A
Regulation	±5%	±5%	±5%	±10%	±5%
Ripple/Noise	50 mV	50 mV	120 mV	120 mV	50 mV

(1) The +3.3V and +5V total output shall not exceed 100W

(2) Maximum combined current for the +12V outputs shall be 62.5A.

MECHANICAL SPECIFICATIONS

