



## FSP1000-57ALC

### Features

- Certified CB 62368
- 80 Plus Platinum Efficiency
- Intel Design ATX 12V V3.1
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

### SAFETY STANDARD APPROVAL



### DESCRIPTION

FSP 57ALC Series features with eco-friendly design, which allows 57ALC series to reach up to 92% efficiency. 57ALC series also equipped with complete protection to prevent your system from damage. 57ALC series does the job efficiently and reliably, making it a stable power supply unit built to satisfy the demands of all kind of system build.

### GENERAL SPECIFICATIONS

<b>Dimension:</b>	140 x 150 x 86 (mm)	<b>Environment</b>	
<b>(L x W x H)</b>	5.51 x 5.91 x 3.39 (inch)	<b>Working temperature:</b>	0°C to 40°C
<b>Efficiency:</b>	80 Plus Platinum Efficiency	<b>Storage temperature:</b>	-20°C to + 70°C
<b>Hold-up time:</b>	115V / 60Hz: ≥ 16ms @80% load 230V / 50Hz: ≥ 16ms @80% load	<b>Working humidity:</b>	~90% RH non-condensing
<b>Operating altitude</b>	5,000 meters above sea level	<b>Storage humidity:</b>	~95% RH non-condensing
<b>MTBF:</b>	100,000 hours of continuous operation at 25°C, Max. output load		

### INPUT SPECIFICATIONS

Input voltage:	100-240Vac
Input frequency:	50-60Hz
Input current:	115 Vac @ 12A, 230 Vac @ 6A

### OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb
Max	20A	20A	83.33A	0.3A	3A
Min.	0A	0A	0A	0A	0A
Regulation	±5%	±5%	±3%	±3%	±5%
Ripple/Noise	40 mV	40 mV	80 mV	80 mV	50 mV

- (1) The +3.3V and +5V total output shall not exceed 100W.
- (2) Maximum combined current for the +12V outputs shall be 83.33A.

### MECHANICAL SPECIFICATIONS

