



FSP1350-57ALB

Features

- Certified CB 62368-1
- 80 Plus Titanium Efficiency
- Intel Design ATX 12V V3.1
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

SAFETY STANDARD APPROVAL



DESCRIPTION

FSP 57ALB Series features with eco-friendly design, which allows 57ALB series to reach up to 94% efficiency. 57ALB series also equipped with complete protection to prevent your system from damage. 57ALB series does the job efficiently and reliably, making it a stable power supply unit built to satisfy the demands of all kind of system build.

GENERAL SPECIFICATIONS

Dimension: 180 x 150 x 86 (mm)
(L x W x H) 7.09 x 5.91 x 3.39 (inch)
Efficiency: 80 Plus Titanium Efficiency

Hold-up time: 115V / 60Hz: ≥ 16ms
230V / 50Hz: ≥ 16ms
Operating altitude 5,000 meters above sea level

MTBF: 100,000 hours of continuous operation at 25°C, Max. output load

Environment

Working temperature: 0°C to 50°C

Storage temperature: -40°C to + 70°C

Working humidity: ~90% RH non-condensing

Storage humidity: ~90% RH non-condensing

INPUT SPECIFICATIONS

Input voltage: 100-240Vac
Input frequency: 50-60Hz
Input current: 115 Vac @ 15A, 230 Vac @ 8A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb
Max	20A	20A	112.5A	0.3A	4A
Min.	0A	0A	0A	0A	0A
Regulation	±1%	±1%	±3%	±10%	±1%
Ripple/Noise	30 mV	30 mV	60 mV	100 mV	30 mV

(1) The +3.3V and +5V total output shall not exceed 120W.

(2) Maximum combined current for the +12V outputs shall be 137.5A.

MECHANICAL SPECIFICATIONS

