

FSP2700-22HM

FEATURES

- Certified CB 62368-1
- Meet 80 Plus Titanium
- Meet M-CRPS Standard
- Meet PMBus 1.2 with Maximum 1% Accuracy
- Support HVDC Input
- Inrush Current Control
- iTHD Control
- Peak Power Capability
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Input/Output Warning and Protection
- FAN Reversed Optional



SAFETY STANDARD APPROVAL



DESCRIPTION

FSP2700-22HM is a redundant power supply module base on M-CRPS standard. The power supply comes to offer the total power capacity up to 2700 Watts, and provides PMBus features, which makes it to be able communicate with motherboard. In addition, the power supply is ideally the best choice for datacenter, workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

GENERAL SPECIFICATIONS

Dimension (L x W x H):	185 x 73.5 x 39 (mm) 7.28 x 2.89 x 1.53 (inch)	Environment	Working temperature: -5°C to 55°C Storage temperature: -40°C to +70°C Working humidity: To 85% RH non-condensing Storage humidity: To 95% RH non-condensing
Efficiency:	80 Plus Titanium	MTBF (SR-332 Issue 2):	250,000 hours of continuous operation at 55°C, 75% output load
Hold-up time:	Max. load >11ms	Applications:	Edge AI, AI Server
Operating altitude:	5,000 meters above sea level		

INPUT SPECIFICATIONS

Input voltage:	90-264Vac or 200Vdc-310Vdc
Input frequency:	47-63Hz

OUTPUT RATING

Outputs	Input Voltage	Min. Current	PL1 Max. Current	PL2 20 Sec. duration	PL3 10m Sec. duration	PL4 200µ Sec. duration
+12V	90~140V	1A	82A	95A	127A	136A
+12V	200~264V	1A	225A	259A	349A	372A
+12Vsb	90~264V	0A	3.0A	3.5A	NA	NA

MECHANICAL SPECIFICATIONS

UNIT: mm

